

30W COMPACT COLOUR RGB IP65 FLOODLIGHT WITH REMOTE CONTROL

ILFLRGB030



Our new RGB floodlight is perfect for environments where you want to add colour for a special occasion or to create impact. At 30W it delivers enough light to make a statement and punch enough light out. It is IP65 and suitable for indoor and outdoor use.

Details

Quick Order Code:	387763
Barcode:	5055788253662
Range Name:	Compact Tough Colour RGB
Product Body Finish:	Matt Black
Market Segment:	Commercial indoor, Residential indoor, Outdoor
Warranty (Years):	2
CE RoHS:	Yes

Physical Data

Product Length (mm):	147
Product Depth (mm):	40
Product Width (mm):	138
Product Weight (g):	400
Optic:	Clear Refractor
Material:	Aluminium, Polycarbonate, Tempered glass
Construction:	Die Cast Aluminium
Bulb or Luminaire Shape:	Rectangle
Luminaire Fixing:	Wall
Placement / Application:	Indoor, Outdoor, General Lighting
Spot Type:	SMD

Electrical Data

Power Consumption (w):	30
Power Factor:	0.5
Input Voltage (V):	220-240
Dimming:	Dimmable with remote controller
Driver Included:	Yes
Electric Current:	AC
Protection Function:	open circuit, short circuit

EN: EN-60598
LVD Certified: Yes

Light Data

Luminous Flux in Lumens (lm): 1200
Beam Angle: 110
Colour Rendering Index (CRI): 80
Colour Type: RGB
Instant on (Less than 1 second): Yes
LED Size (mm): 2835
LED Type: Surface mounted device (SMD)
Lifetime (hours): 35000
Lighting Method: Back-lit
Switching Cycles: 17500

Environment

EN: EN-60598
LVD Certified: Yes
CE RoHS: Yes
Hg 0% (Mercury Free): Yes
IK Rating (Impact Protection): IK07
IP Rating (Back/Recessed side): IP65
IP Rating (Ingress Protection): IP65
Lowest Operating Temperature (°C): -25
Maximum Operating Temperature (°C): 45

Packaging

Package Weight (g): 551
Package Length (mm): 165
Package Width (mm): 170
Package Depth (mm): 55