Xnightsbridge


DATASHEET



TORCW6

230V IP65 IK08 6ft Selectable 30W/60W CCT Adjustable Non-Corrosive

www.mlaccessories.co.uk



MLA PART CODE	TORCW6
DESCRIPTION	230V IP65 IK08 6ft Selectable 30W/60W CCT Adjustable Non- Corrosive
NET WEIGHT (KG)	2.42
FINISH	Grey
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 1828 Width - 90 Projection - 90
CONSTRUCTION	Construction - Polycarbonate
CLASS	I
IP RATING	IP65
IK RATING	IK08
WATTAGE (W)	30/60
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	4300/4750/4560, 7475/8660/8040
LUMENS LIGHT SOURCE ONLY (LM)	10000
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	161.8
CIRCUIT WATTAGE (W)	30.6/60.3
ССТ	3000/4000/5700K
LIGHT COLOUR	ССТ
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.28
DISPLACEMENT FACTOR	>0.9
SVM	0.017
PST-LM	0.028
BEAM ANGLE (DEGREES)	150





Xnightsbridge

LIFE SPAN (HRS)	50,000
L70B50 LIFESPAN (HRS)	60000
DIMMABLE	No
OPERATING TEMPERATURE	-20~40°C
INPUT VOLTAGE	230V 50Hz
CABLE ENTRY (MM)	20
CABLE GLAND INCLUDED	Compression gland
DRIVER	EFFICIENCY FULL LOAD - 95.2
WARRANTY	5year(s)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270851557

Date Created: 18/01/2023 13:30





