



DATASHEET



TORCWST5

230V IP65 IK08 5ft Selectable 26W/48W CCT
Adjustable ST Emergency Non-Corrosive

www.mlaccessories.co.uk



MLA PART CODE	TORCWST5
DESCRIPTION	230V IP65 IK08 5ft Selectable 26W/48W CCT Adjustable ST Emergency Non-Corrosive
NET WEIGHT (KG)	2.24
FINISH	Grey
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 1563 Width - 90 Projection - 90
CONSTRUCTION	Construction - Polycarbonate
CLASS	I
IP RATING	IP65
IK RATING	IK08
WATTAGE (W)	26/48
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	3810/4045/4030, 6230/7250/6800
LUMENS LIGHT SOURCE ONLY (LM)	8085
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	167.5
LUMENS EMERGENCY MODE (LM)	320
CIRCUIT WATTAGE (W)	25.6/48.4
CCT	3000/4000/5700K
LIGHT COLOUR	CCT
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.21
DISPLACEMENT FACTOR	>0.9
SVM	0.019
PST-LM	0.044

BEAM ANGLE (DEGREES)	140
LIFE SPAN (HRS)	50,000
L70B50 LIFESPAN (HRS)	60000
DIMMABLE	No
EMERGENCY	Maintained / Non-maintained / Switched
SELF-TEST	Yes
OPERATING TEMPERATURE	-5~40°C
INPUT VOLTAGE	230V 50Hz
CABLE ENTRY (MM)	20
CABLE GLAND INCLUDED	Compression gland
DRIVER	EFFICIENCY FULL LOAD - 88.4
BATTERY INCLUDED	Yes
WARRANTY	5year(s)
WARRANTY INFORMATION	(excluding battery)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270851588

Date Created: 18/01/2023 13:57

