

EVOFIRE FIRE RATED DOWNLIGHT 70-100MM CUTOUT IP65 WHITE ROUND +GU10 HOLDER INTEGRAL

ILDLFR70D015



The Evofire Fire Rated Downlight is a safe and attractive fitting for a GU10 or MR16 LED lamp. The fully open design of the Evofire does not conceal your lamp in a large metal canister, which can trap some of the heat it generates, lowering lamp lifetime and performance. Lamps installed in an Evofire run at up to 10 degrees C cooler than a typical can-style fire rated downlight from leading LED brands - this can extend the lifetime of your lamps. As well being very tough thanks to its steel construction, The Evofire is also a highly aesthetic choice for Fire Rated lighting. The 1mm blend-in bezel is up to 10 times thinner than typical IP65 rated downlights, has a high quality powder coating and fits almost flush with your ceiling, so the downlight looks discreet and pleasing in any setting. This downlight is fire rated to 30, 60 and 90 minutes in compliance with BS476 Part 21:1987, Air Tightness compliant with Part C and Part L and Resistance to Sound compliant with Part E. See installation guide for full details. Evofire shown with Real Colour GU10 LED lamp (sold separately).

Perfect for installing downlights in low-profile areas.

Example: Use ILDLFR70D001 + ILMDC001 to achieve a profile as low as 38.5mm

Evolight fitted in a downlight

Details

Quick Order Code:	561100
Barcode:	5055788236481
Category:	Downlights
Range Name:	Evofire
Product Type:	Fire Rated
Product Body Finish:	Matt white
Market Segment:	Commercial indoor, Residential indoor
Finish:	Matt White
Fixed/Tilttable:	Fixed
Warranty (Years):	3
CE RoHS:	Yes

Physical Data

	38
Product Depth (mm):	166
Product Weight (g):	Steel, Glass
Material:	110
Overall diameter (mm):	Pressed Steel, Glass
Construction:	70-100
Cut Out Diameter (mm):	Round
Bulb or Luminaire Shape:	Recess mounted
Luminaire Fixing:	Indoor, General Lighting
Placement / Application:	

Electrical Data

Insulation Guard:	No
--------------------------	----

Light Data

Fire Rating (mins):	30, 60, 90
----------------------------	------------

Environment

CE RoHS:	Yes
IP Rating (Ingress Protection):	IP65

Packaging

Package Weight (g):	181
Package Length (mm):	115
Package Width (mm):	115
Package Depth (mm):	70