


## DATASHEET



### BT14ACTEM

230V IP65 14W CCT Adjustable LED Bulkhead with Emergency

[www.mlaccessories.co.uk](http://www.mlaccessories.co.uk)



MLA PART CODE	BT14ACTEM
DESCRIPTION	230V IP65 14W CCT Adjustable LED Bulkhead with Emergency
NET WEIGHT (KG)	1.1
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Diameter - 315 Projection - 74
CONSTRUCTION	Construction - Polycarbonate
CLASS	II
IP RATING	IP65
IK RATING	IK08
WATTAGE (W)	14
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	1130 / 1260 / 1210
LUMENS LIGHT SOURCE ONLY (LM)	1340
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	109.9
LUMENS EMERGENCY MODE (LM)	180
CIRCUIT WATTAGE (W)	12.19
CCT	3000/4000/5700K
LIGHT COLOUR	CCT
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.058
DISPLACEMENT FACTOR	>0.9
SVM	0.567
PST-LM	0.027
BEAM ANGLE (DEGREES)	115

<b>LIFE SPAN (HRS)</b>	30,000
<b>L70B50 LIFESPAN (HRS)</b>	50,000
<b>LED COMPATIBLE</b>	Yes
<b>DIMMABLE</b>	No
<b>EMERGENCY</b>	Maintained / Non-maintained / Switched
<b>OPERATING TEMPERATURE</b>	-20~50°C
<b>INPUT VOLTAGE</b>	230V 50Hz
<b>CABLE ENTRY (MM)</b>	20
<b>CABLE GLAND INCLUDED</b>	Blind grommet
<b>DRIVER</b>	DRIVER TYPE - Constant Current MAX. OUTPUT - 14W OUTPUT VOLTAGE - 30 - 43V OUTPUT CURRENT - 320mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 83 ISOLATION - SELV AMBIENT TEMPERATURE (Ta) - -20~50°C CASE TEMPERATURE (Tc) - 75°C
<b>BATTERY INCLUDED</b>	Yes
<b>WARRANTY</b>	5year(s)
<b>WARRANTY INFORMATION</b>	(excluding battery)
<b>MANUFACTURED IN ACCORDANCE WITH</b>	BS EN 60598
<b>ORIGIN OF MANUFACTURE</b>	China
<b>DECLARATION OF CONFORMITY (HELD ON FILE)</b>	Yes
<b>EAN</b>	5056270825404

Date Created: 21/04/2023 13:57

