

Technical Data

25 Amp Flex Outlet Plate

Brief product description:

The subtle design will blend with any décor - suitable for domestic or commercial installations.

Features:

- White moulded round edge, sleek and slim with softly rounded edges
- Easy to install, supplied with fixing screws and installation instructions
- Twin Earth for high integrity circuits
- Cable entry in lower edge with removable reducer and reversible cord grip
- Angled terminals with captive, backed out screws for fast installation
- Screw cover caps for a sleek appearance
- Anti-microbial certified manufactured using high grade thermoset Urea which effectively inhibits the growth of infectious diseases, including MRSA, E-Coli, Salmonella and Klebsiella Pneumonia bacteria

Product Images








858

Technical Specifications		
Standard(s)	BS 5733	UK
Rating	25 Amp 250V AC	CA
Terminal Capacity	2 x 2.5mm ² 1 x 4.0mm ²	$C \in$
RoHS Directive	Yes	
WEEE Directive	Yes	
Mounting Box Depth (Min)	25mm	
Fixing Centres	60.3mm	



25 Amp Flex Outlet Plate

Line Diagrams





Packaging Information

Cat No.	Description	Packaging Type			Pack Quantity			Barcode		
		Product	Inner Box	Outer Box	Each	Inner Box	Outer Box	Individual	Inner Box	Outer Box
858	FLEX OUTLET PLATE	Printed Bag	Printed Carton	Printed Carton	1	10	100	5050765001694	5050765001700	5050765001717

Weights & Dimensions

Cat	No.	Description	Dimensions (H x W x D) cm				Weight (kg)				CBM (m³)
			Unpacked Product	Packed Product	Inner Box	Outer Box	Unpacked Product	Packed Product	Inner Box	Outer Box	Outer Box
858		FLEX OUTLET PLATE	8.6 x 8.6 x 2.7	16.5 x 11.0 x 2.8	9.5 x 12.7 x 18.2	20.1 x 26.3 x 50.3	0.078	0.082	1.06	10.88	0.02659