

Technical Data

13 Amp Power Socket with USB Charger

Brief product description:

Free up your sockets using the White Moulded Socket with USB charger capability ideal for charging iPad, iPhone, tables, mobiles, cameras and


Features:

- 13A Power Sockets with integrated USB-A ports
- Smart Charging Intelligently adjusts the voltage to give devices the power they need, when they need it, without overcharging
- White moulded square edge profile offering exceptional value
- Power socket for standard 3 pin UK plug
- Easy to install, supplied with fixing screws and installation instructions
- Angled in-line colour coded terminals with backed out screws for fast installation
- Screw cover caps for a sleek appearance
- Twin earth fitted as standard for high integrity circuits
- Anti-microbial certified manufactured using high grade thermoset Urea which effectively inhibits the growth of infectious diseases, including MRSA, E-Coli, Salmonella and Klebsiella Pneumonia bacteria

Product Images




921U2









922U3







922U33

924U44

Line Diagrams







13 Amp Power Socket with USB Charger

Standard(s)	BS 1363-2:2016+A1:2018	Ų					
Rating	13 Amp 240V ~						
Switch Type	Single Pole (924U44 Unswitched)	(
Terminal Capacity - L & N	3 x 2.5mm², 3 x 4.0mm² & 2 x 6.0mm²						
RoHS Directive	Yes						
WEEE Directive	Yes						
Mounting Box Depth (Min)	25mm	Lie					
Fixing Centres	60.3mm (921U2 products)						
	120.6mm (922U3, 922U33, 924U44 products)						
USB Output	921U2 5V, 2.1A, shared across two USB ports						
	922U3 5V, 3.1A, shared across two USB ports						
	922U33 5V, 3.1A, shared across three USB ports						
	924U44 5V, 4.2A, shared across four USB ports						
Output Tolerance	<5%						
Standby Power	<75mW						
USB Overcurrent Protection	921U2 ≦2.43A						
	922U3 ≦3.60A						
	922U33 ≦3.60A						
	924U44 ≦4.85A						

Packaging Information											
Cat No.	Description	Packaging Type			Pack Quantity			Barcode			
		Product	Inner Box	Outer Box	Each	Inner Box	Outer Box	Individual	Inner Box	Outer Box	
921U2	1G, 2 x USB (2.1A)	Printed Bag	Printed Carton	Printed Carton	1	10	100	5050765114349	5050765117548	5050765117807	
922U3	2G, 2 x USB (3.1A)	Printed Bag	Printed Carton	Printed Carton	1	5	50	5050765136846	5050765142588	5050765142779	
922U33	2G, 3 x USB (3.1A)	Printed Bag	Printed Carton	Printed Carton	1	5	50	5050765137164	5050765137164	5050765142984	
924U44	2G, 4 x USB (4.2A)	Printed Bag	Printed Carton	Printed Carton	1	5	50	5050765136853	5050765143004	5050765143189	

Weights & Dimensions										
Cat No.	Description	Dimensions (H x W x D) cm				Weight (kg)				CBM (m³)
		Unpacked Product	Packed Product	Inner Box	Outer Box	Unpacked Product	Packed Product	Inner Box	Outer Box	Outer Box
921U2	1G, 2 x USB (2.1A)	8.6 x 8.6 x 3.0	18.0 x 11.0 x 3.2	9.5 x 18.7 x 16.7	21.6 x 49.0 x 35.6	0.116	0.120	1.29	13.35	0.03768
922U3	2G, 2 x USB (3.1A)	8.6 x 14.6 x 3.3	23.0 x 12.0 x 3.5	9.3 x 15.2 x 15.7	17.6 x 31.3 x 49.8	0.186	0.191	1.02	10.62	0.02743
922U33	2G, 3 x USB (3.1A)	8.6 x 14.6 x 3.3	23.0 x 12.0 x 3.5	9.3 x 16.7 x 14.2	18.1 x 48.5 x 29.3	0.191	0.196	1.03	10.80	0.02572
924U44	2G, 4 x USB (4.2A)	8.6 x 14.6 x 2.7	23.0 x 12.0 x 2.9	9.3 x 16.7 x 14.2	18.1 x 48.5 x 29.3	0.189	0.194	1.02	10.66	0.02572