
Illuma

Technical Data Sheet

| Range Name: | Lumapar |
|---------------------------|--|
| Product Type: | Spotlights |
| Product Code: | T340506-WH/SDL/830 |
| | 13-6506 WH/SDE/656 |
| Body Colour: | White |
| Mounting: | Track Mounted |
| Track Adaptor: | SDL - 1-Circuit Switched Track Adaptor |
| Pendant Stem Length(mm): | - |
| Vertical Mount: | - |
| Environment: | Interior |
| Size(mm) | 120 x 87 x 60 |
| Cut Out(mm): | - |
| Recessed Depth(mm): | - |
| Vertical Tilt(°): | 90° |
| Horizontal Rotation(°): | 355° |
| Light Source: | LED |
| Lamp Type: | CREE LED |
| Lamp Included: | In Built |
| Lamp Base: | - |
| Lamp Life(Hours): | 50000 hours |
| Lumen Output(Im): | 500lm |
| Colour Temperature(k): | 3000k Warm White |
| CRI(Ra): | 82 |
| Beam Angle(°): | 6° |
| Lense: | - |
| Voltage(V): | 230VAC |
| Total System Power(W): | 7.7W |
| Lamp Current(A): | 0.035 |
| Power Factor: | - |
| Luminaire Efficacy(Im/W): | 51 lm/W |
| Class: | Class 1 |
| Gear: | Built In |
| EAN Code: | - |
| Dimmability: | Leading/Trailing Edge Dimmable |
| Emergency: | - |
| IP Rating: | IP20 |
| Weight(kg): | 0.3kg |
| Housing Material: | Aluminium |
| Material Finish: | Powder Coated |
| Guarantee: | 5 Year Guarantee |
| | |





Images, line drawings and measurements illustrated may, in some cases be approximate and for guidance only. Colour finishes will be maintained as accurately as possible but matching cannot be guaranteed. Illuma Lighting are continually developing and improving its products. Technical specifications subject to change without prior notice. For full terms and conditions visit: <u>https://www.illuma.co.uk/terms.htm</u>

Illuma Lighting (*Trading as a divison of Searchlight Electric Ltd.*) Sills Road, Willow Farm Business Park Castle Donington Derbyshire, DE74 2US United Kingdom © Illuma 2021

T +44(0) 1332 818 200 F +44(0) 1332 818 222 E sales@illuma.co.uk W www.illuma.co.uk

VAT Registration No. 149697311 Registered in England No: 1169504 Certification BS EN ISO 9001:2008