

REAL COLOUR GU10 BULB 400LM 5W 3000K DIMMABLE 36 BEAM CRI95 INTEGRAL

ILGU10DD112



Rich reds, pretty pinks, gorgeous greens - Integral Real Colour GU10 Spotlights utilise a chip-on-board LED with high colour rendering (CRI 95) to bring out the colour in any space - including homes, retail businesses, galleries and showrooms. Your colours will appear more vibrant and better defined than with a standard LED spotlight (CRI 80) - ideal for showing colourful furniture, artwork, fashion, food and other retail products at their best. The crystal-effect lens adds a retro sparkle that delivers a diffused light and looks good when the lamp is on or off.

Details

Quick Order Code: 428362

Barcode: 5055788252726

Category:LampsRange Name:Real ColourProduct Type:GU10Product Body Finish:Glass

Market Segment: Commercial indoor, Residential indoor

Warranty (Years): 2
CE RoHS: Yes

Physical Data

Product Length (mm): 54
Product Width (mm): 50
Product Weight (g): 44

Optic: Designed to give a Halogen look

Material:GlassBase Term:GU10Bulb Base:GU10Construction:Glass bodyBulb Fixing:DownlightBulb or Luminaire Shape:Round

Placement / Application: Indoor, General Lighting

Spot Type: SMD

Electrical Data

5

Power Consumption (W):

Power Factor:

Voltage Range (v):

Wattage equivalent (W):

0.5

220-240

50

31

Amperage (mA):DimmableDimming:SilergyDriver IC Manufacturer:YesDriver Included:ACElectric Current:50

True Wattage Eq (W): EN-62560

EN: Yes

LVD Certified: Light Data

Luminous Flux in Lumens (Im): 400
Luminous efficacy (Im/W): 80
Peak Intensity (Cd): 600
Correlated Colour Temperature (CCT) (K): 3000

Colour Temperature: 3000K - Warm White

Colour Temperature Name: Warm White

Beam Angle: 36 **Colour Rendering Index (CRI):** 95

Compatible Dimmers: Varilight JQP401W

Frequency Range (Hz): 50
Instant on (Less than 1 second): Yes


LED Type: Surface mounted device (SMD)


Lifetime (hours): 15000
Switching Cycles: 7500
Useful Lumens (lm): 345

Environment

EN: EN-62560

LVD Certified: Yes
CE RoHS: Yes
Previous Energy Rating: A+
New Energy Rating: G
Hg 0% (Mercury Free): Yes
Lowest Operating Temperature (°C): -25
Maximum Operating Temperature (°C): 40





Packaging

Package Weight (g): 69
Package Length (mm): 60
Package Width (mm): 55
Package Depth (mm): 55
Qty per euro pallet: 2100