

Product data sheet

Characteristics

GGBL3080

Lisse White moulded - socket-outlet - 5 A - 1 gang - matt white set of 10



Main

Commercial Status	Commercialised
Range	Lisse
Aesthetic name	White moulded
Product or component type	Socket-outlet
Device presentation	Complete product
Outlet standard description	Round pin
Switch function	Unswitch
Colour tint	White matt
Quantity per set	Set of 10

Complementary

Outlet poles configuration	1P
Outlet standard	British
Number of gangs	1 gang
Device mounting	Wall mounted
Rated current	5 A, 230 V AC 50 Hz :
Fixing mode	By screws M3.5 25 mm
Connections - terminals	Screw terminals
Material	Urea (carbamide)
Type of packing	Carton
Type of installation	Indoor
Height	26.6 mm
Width	87 mm
Depth	87 mm
Product weight	0.071 kg

Environment

Standards	BS 546
IP degree of protection	IP20

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.