

# MAYFAIR ADJUSTABLE 5744

SKU 1377002

astro



## PRODUCT SPECIFICATION

### GENERAL

<b>FINISH:</b>	White	<b>CABLE LENGTH:</b>	0.45 (mm)
<b>MAIN MATERIAL:</b>	Metal - Aluminium	<b>GROSS WEIGHT:</b>	0.32 (kg)
<b>DIMENSIONS:</b>	DIA: 87mm D: 94mm	<b>CLASS:</b>	CE (Class III)
<b>INSTALLATION ORIENTATION:</b>	Ceiling Mount	<b>IP RATING:</b>	IP65
<b>CUT OUT HOLE:</b>	73mm/2-7/8"	<b>BATHROOM ZONE:</b>	Zone 1, 2, 3
<b>RECESS DEPTH:</b>	114 (mm)	<b>VOLTAGE:</b>	Constant Current 700 (mA)
<b>FIRE RATING:</b>	Not Applicable	<b>PRODUCT F MARK:</b>	Not suitable for covering with thermal insulation

### LAMP

<b>LIGHT SOURCE:</b>	COB LED	<b>MACADAM ELIPSE:</b>	4-Step
<b>MAXIMUM WATTAGE:</b>	7.4W	<b>UGR:</b>	To Be Advised
<b>MAXIMUM LAMP LENGTH:</b>	Not Applicable	<b>BEAM ANGLE:</b>	25 (Degrees)
<b>LAMP INCLUDED?</b>	Yes	<b>TILT ADJUSTMENT ANGLE:</b>	45 (Degrees)
<b>LUMINOUS FLUX:</b>	304.99 (lm)	<b>ROTATION ADJUSTMENT ANGLE:</b>	360 (Degrees)
<b>COLOUR TEMP:</b>	2700 (K)	<b>AVERAGE LIFESPAN:</b>	36,300 (Hrs)
<b>CRI:</b>	80	<b>L70:</b>	To Be Advised
<b>R9:</b>	5.0		


### ELECTRICAL

<b>SWITCHED:</b>	No	<b>SUPPLY FREQUENCY:</b>	Not Applicable
<b>DIMMABLE:</b>	Yes	<b>DRIVER/BALLAST VOLTAGE:</b>	Not Applicable
<b>DIMMING METHOD:</b>	Control Gear Dependant	<b>DRIVER AVERAGE LIFESPAN:</b>	Not Applicable
<b>DRIVER OUTPUT CURRENT:</b>	Not Applicable	<b>EFFICACY:</b>	31.54 (lm/W)
<b>DRIVER OUTPUT VOLTAGE:</b>	Not Applicable	<b>DRIVER/BALLAST INCLUDED?</b>	Not applicable

## ADDITIONAL INFORMATION



Tested with 1836 driver



BOX QUANTITY X20

# PRODUCT ELEVATIONS



73mm/2-7/8"

