

ELIS TWIN 7202

SKU 1331002

astro



PRODUCT SPECIFICATION

GENERAL

FINISH:	Textured Black	CABLE LENGTH:	Not Applicable
MAIN MATERIAL:	Metal - Aluminium	GROSS WEIGHT:	0.89 (kg)
DIMENSIONS:	H: 141mm W: 141mm D: 51mm	CLASS:	CE (Class I)
INSTALLATION ORIENTATION:	Ceiling Mount (reduced IP rating) / Wall Mount	IP RATING:	IP54
CUT OUT HOLE:	Not Applicable	BATHROOM ZONE:	Zone 2, 3
RECESS DEPTH:	Not Applicable	VOLTAGE:	Mains 230 (V)
FIRE RATING:	Not Applicable	PRODUCT F MARK:	Suitable for mounting on flammable materials

LAMP

LIGHT SOURCE:	High Power LED	MACADAM ELIPSE:	6-Step
MAXIMUM WATTAGE:	7.7W Max	UGR:	Not Applicable
MAXIMUM LAMP LENGTH:	Not Applicable	BEAM ANGLE:	To Be Advised
LAMP INCLUDED?	Yes (Integral)	TILT ADJUSTMENT ANGLE:	Not Applicable
LUMINOUS FLUX:	490.41 (lm)	ROTATION ADJUSTMENT ANGLE:	Not Applicable
COLOUR TEMP:	3000 (K)	AVERAGE LIFESPAN:	60,500 (Hrs)
CRI:	80	L70:	To Be Advised
R9:	10.0		


ELECTRICAL

SWITCHED:	No	SUPPLY FREQUENCY:	50/60 (Hz)
DIMMABLE:	No	DRIVER / BALLAST VOLTAGE:	100-240 (V)
DIMMING METHOD:	Not Applicable	DRIVER AVERAGE LIFESPAN:	25,000 (Hrs)
DRIVER OUTPUT CURRENT:	350 (mA)	EFFICACY:	63.69 (lm/W)
DRIVER OUTPUT VOLTAGE:	Not Applicable	DRIVER / BALLAST INCLUDED?	Yes (Integral)

ADDITIONAL INFORMATION



 1000 HOURS SALT-SPRAY TESTED



BOX QUANTITY x 30

PRODUCT ELEVATIONS

