Product datasheet Characteristics

GU3030RD

Ultimate Slimline - switched socket - 2P - 2 gangs - red



Main		
Aesthetic name	Slimline	
Product or component type	Switched socket	
Rated current	13 A at 230 V AC 50 Hz	
Fixing mode	By screws M3.5 x	
Colour tint	Red moulded matt	

Complementary

Device presentation	Complete product	4
Outlet poles configuration	2P	
Outlet standard description	3 pins	<u></u>
Outlet standard	British	i i
Actuator	Rocker	: I
Number of gangs	2 gangs	. in
Earth circuit	Standard earth	Ę
Pilot light	Without neon indicator	
Device mounting	Wall mounted	9
Connections - terminals	Screw terminal	
Material	Urea (carbamide)	+
Quantity per set	Set of 5	
Height	86 mm	ů.
Width	146 mm	ch chia in in
Depth	30 mm	2

Environment

IP degree of protection	IP20	—. <u>=</u>
Standards	BS 1363	<u>ب</u> .و

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	ner: This c
Mercury free	Yes	sclain———

RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
Contractual warranty	
Warranty	18 months