

Screwless 2-Way Matt Black Dimmer



Push on/push off control. Advanced trailing edge type dimmer suitable for dimming all types of lamps both resistive and inductive. Minimum capacity: 5W dimmable LED or 10W incandescent. Maximum capacity: 150W dimmable LED or 200W incandescent. Suitable for mains lighting, low voltage lighting and LED lighting (for compatibility please check with lamp manufacturer).

MLA part code	SF2183MBB	SF2184MBB
Description	Screwless 3G 2-way dimmer	Screwless 4G 2-way dimmer
Finish	Matt Black	
Nett weight (kg)	0.383	0.436
Dimensions (mm)	Height – 87.5 Width – 148.5 Projection – 4.3	
Minimum mounting depth (mm)	25	
Input voltage	Mains 230V 50Hz	
Maximum load	Halogen / GLS – 10W to 200W LED – 5W to 150W	
Dimmer type	Trailing Edge	
Terminal capacity	2 x 1.0mm ² or 2 x 1.5mm ²	
Construction	Premium grade steel	
Class	Class I	
IP rating	IP20	
Warranty	3 Years	
Origin of Manufacture	China	
Declaration of Conformity (held on file)	Yes	
Manufactured in accordance with	BS EN 60669-2	
EAN	5055832988175	5055832993391