

APRILIA TWIN ADJUSTABLE 5763

SKU 1256028

astro



PRODUCT SPECIFICATION

GENERAL

FINISH:	Anodised Aluminium	CABLE LENGTH:	450 (mm)
MAIN MATERIAL:	Metal - Aluminium	GROSS WEIGHT:	0.682 (Kg)
DIMENSIONS:	H: 180mm W: 95mm D: 69mm	CLASS:	CE (Class III)
INSTALLATION ORIENTATION:	Ceiling Mount	IP RATING:	IP21
CUT OUT HOLE:	L: 165mm W: 85mm	BATHROOM ZONE:	Zone 3
RECESS DEPTH:	150 (mm)	VOLTAGE:	Constant Current 350 (mA)
FIRE RATING:	Not Applicable	PRODUCT F MARK:	Suitable for mounting on flammable materials

LAMP


LIGHT SOURCE:	COB LED	MACADAM ELLIPSE:	3-Step
MAXIMUM WATTAGE:	2 x 6.1W	UGR:	To Be Advised
MAXIMUM LAMP LENGTH:	Not Applicable	BEAM ANGLE:	36.1 (Degrees)
LAMP INCLUDED?	Yes (Integral)	TILT ADJUSTMENT ANGLE:	35 (Degrees)
LUMINOUS FLUX:	1206.1 (lm)	ROTATION ADJUSTMENT ANGLE:	360 (Degrees)
COLOUR TEMP:	3000 (K)	AVERAGE LIFESPAN:	36,300 (Hrs)
CRI:	80	L70:	To Be Advised
R9:	13.0		

ELECTRICAL

SWITCHED:	No	SUPPLY FREQUENCY:	Not Applicable
DIMMABLE:	Yes	DRIVER/BALLAST VOLTAGE:	Not Applicable
DIMMING METHOD:	Control Gear Dependant	DRIVER AVERAGE LIFESPAN:	Not Applicable
DRIVER OUTPUT CURRENT:	Not Applicable	EFFICACY:	97.27 (lm/W)
DRIVER OUTPUT VOLTAGE:	Not Applicable	DRIVER/BALLAST INCLUDED?	No

ADDITIONAL INFORMATION

CE



BOX QUANTITY x 20

PRODUCT ELEVATIONS

