

Socket Outlets

Connection Units

NON STANDARD
13 AMP
SURFACE

13 AMP
SURFACE

ROUND PIN
SURFACE

15 AMP
127V
SURFACE

SWITCHED
FUDED
SURFACE



K1247 ALM



K1247 D6 ALM



K1248 ALM



K1248 D6 ALM



K848 ALM



K850 ALM



K841 ALM



K842 ALM



K843 ALM



K2271 ALM



K2272 ALM



K963 KO ALM



K942 ALM



K962 ALM



K962 D6 ALM

K1247 ALM

1 GANG DP WITH CLEAN EARTH FACILITY

K1247D6ALM

1 GANG DP WITH RED ROCKER AND CLEAN EARTH FACILITY

K1248 ALM

2 GANG DP WITH CLEAN EARTH FACILITY

K1248D6ALM

2 GANG DP WITH RED ROCKERS AND CLEAN EARTH FACILITY

These products are provided with facilities for 'clean earth' connection and are suitable for non standard plugs with 'T' shaped earth pin. Earth terminal fitted in boxes.

DIMENSIONS:

1 gang: 86 x 86 x 51mm

2 gang: 86 x 146 x 51mm

TERMINAL CAPACITY:

2 x 6mm² stranded (max)

KNOCKOUTS:

1 gang 6 x 20mm.

Two in one side and one in each of other three sides. One in base

2 gang 8 x 20mm.

Three in top, two in bottom sides and one in each end. One in base

Spare Boxes with and without knockouts are available.

All boxes have a base knockout

BS.1363 Pt.2: 1995 where relevant

5

1

5

1

K848 ALM

1 GANG

K850 ALM

2 GANG WITH DUAL EARTH TERMINALS

K850 ALM has two earth terminals providing a double earth facility when installations are to comply with Section 607 of BS 7671 IEE Wiring Regs. Earth terminal fitted in box.

DIMENSIONS:

1 gang 86 x 86 x 47mm

2 gang 86 x 146 x 47mm

TERMINAL CAPACITY:

2 x 6mm² stranded (max)

KNOCKOUTS:

1 gang 6 x 20mm.

Two in one side and one in each of other three sides. One in base

2 gang 8 x 20mm.

Three in top, two in bottom sides and one in each end. One in base

Spare Boxes with and without knockouts are available.

All boxes have a base knockout

BS.1363 Pt.2: 1995

5

5

K841 ALM

1 GANG

2 AMP SHUTTERED

K842 ALM

1 GANG

5 AMP SHUTTERED

K843 ALM

1 GANG

15 AMP SHUTTERED

Earth terminal fitted in box.

DIMENSIONS:
86 x 86 x 47mm

TERMINAL CAPACITY:

2 amp:

3 x 2.5mm² (max)

5 amp:

2 x 6mm² stranded (max)

15 amp

2 x 6mm² stranded (max)

KNOCKOUTS:

6 x 20mm.

Two in one side and one in each of other three sides. One in base

Spare Boxes with and without knockouts are available.

All boxes have a base knockout.

BS.546: 1950

5

5

5

K2271 ALM

1 GANG SHUTTERED (NON UK)

K2272 ALM

2 GANG SHUTTERED (NON UK)

Earth terminal fitted in box.

DIMENSIONS:
1 gang 86 x 86 x 47mm
2 gang 86 x 146 x 47mm

KNOCKOUTS:

1 gang 6 x 20mm.

Two in one side and one in each of other three sides. One in base

2 gang 8 x 20mm.

Three in top, two in bottom sides and one in each end. One in base

Spare Boxes with and without knockouts are available.

All boxes have a base knockout.

SSA: 444:1985

5

5

5

K963KOALM

DP WITH SECRET KEY OPERATED SWITCH, NEON AND TAMPERPROOF FUSE CARRIER SCREW

K942 ALM

DP SWITCHED

K942D5ALM

DP SWITCHED WITHOUT BOX

K942KOALM

DP SWITCHED WITH TAMPERPROOF FUSE CARRIER SCREW

K962 ALM

DP SWITCHED WITH NEON

K962D6ALM

DP SWITCHED WITH NEON AND RED ROCKER

All connection units are fitted with a 13 amp fuse (to BS.1362.)

Earth terminal fitted in base of the box.

DIMENSIONS: 86 x 86 x 47mm

TERMINAL CAPACITY:

2 x 6mm² stranded(max)

KNOCKOUTS: 5 x 20mm.

Two in one side and one in each of other three sides.

Spare Boxes with and without knockouts are available.

All boxes have a base knockout.

BS.1363 Pt.4: 1995

1

10

1

1

10

1