Illuma

Technical Data Sheet

Track SystemsProduct Type:Track SystemsDescription:Live End-Sliver Grey-Incoming Mains End FeedProduct Code:T38-SGBody Colour:Silver GreyMounting:-Track Adaptor:-Product Sem Length(mm):-Size(mm)82Cut Out(mm):-Size(mm)82Vertical Tilt(*):-Horizontal Rotation(*):-Lamp Type:-Lamp Louded:-Lamp Louded:-Lamp Louded:-Colour Temperature(k):-Power Factor:-Lamp Colour:-Voltage(V):230VTotal System Power(W):-Class:Class 1Gear:-EAN Code:-Sillage Sillage:-Lamp Life(hours):-Colour Temperature(k):-Class:	Range Name:	1-Circuit 230V
Description:Live End-Silver Grey-Incoming Mains End FeedProduct Code:T38-SGBody Colour:Silver GreyMounting:-Track Adaptor:-Pendant Stem Length(mm):-Bize(mm)82Cut Out(mm):-Size(mm)0Kecessed Depth(mm):-Vertical Tilt(°):-Light Source:-Lamp Type:-Lamp Type:-Lamp Life(Hours):-Colour Temperature(k):-Jost-Ketage(r):-Colour Temperature(k):-Lamp Current(A):-Colour Temperature(k):-Colour Temperature(k):- <th>_</th> <th></th>	_	
FeedProduct Code:T38-SGBody Colour:Silver GreyMounting:-Track Adaptor:-Pendant Stem Length(mm)-Bize(mm)82Cut Out(mm):-Size(mm)0Vertical Tilt(°):-Dig Dig Dig Dig Dig Dig Dig Dig Dig Dig		
Body Colour:Silver GreyMounting:-Track Adaptor:-Pendant Stem Length(mm):-Environment:InteriorSize(mm)82Cut Out(mm):-Recessed Depth(mm):-Vertical Tilt(°):-Light Source:-Lamp Type:-Lamp Included:-Lamp Life(Hours):-Colour Temperature(k):-Beam Angle(°):-Lamp Current(A):-Lamp Current(A):-Colour Temperature(k):-Joit System Power(W):-Current(A):-Catage(V)	beschption	, –
Mounting:-Tack Adaptor:-Fack Adaptor:-Pendant Stem Length(mm):-Environment:NateriorSize(mm)-Recessed Depth(mm):-Vertical Tilt(°):-Particontal Rotation(°):-Light Source:-Lamp Type:-Lamp Type:-Lamp Table:-Lamp Included:-Diame Output(Im):-Colour Temperature(k):-Rease:-Colour Temperature(k):-Diame Output(Im):-Diame Output(Im):-Diame Output(Im):-Colour Temperature(k):-Qiame Output(Im):-Colour Temperature(k):-Diame Output(Im):-Colour Temperature(k):-Diame Output(Im):-Colour Temperature(k):-Diame Output(Im):-Diame Output(Im): <th>Product Code:</th> <th>T38-SG</th>	Product Code:	T38-SG
Mounting:-Tack Adaptor:-Fack Adaptor:-Pendant Stem Length(mm):-Environment:NateriorSize(mm)-Recessed Depth(mm):-Vertical Tilt(°):-Particontal Rotation(°):-Light Source:-Lamp Type:-Lamp Type:-Lamp Table:-Lamp Included:-Diame Output(Im):-Colour Temperature(k):-Rease:-Colour Temperature(k):-Diame Output(Im):-Diame Output(Im):-Diame Output(Im):-Colour Temperature(k):-Qiame Output(Im):-Colour Temperature(k):-Diame Output(Im):-Colour Temperature(k):-Diame Output(Im):-Colour Temperature(k):-Diame Output(Im):-Diame Output(Im): <th></th> <th></th>		
Track Adaptor:.Pendant Stem Length(mm):.Interior.Size(mm).Size(mm).Qu Out(mm):.Perdeased Depth(mm):.Vertical Tilt(°):.Jurizontal Rotation(°):.Jurizontal Ro		Silver Grey
Pendant Stem Length(mm):·Environment:InteriorSize(mm)82Cut Out(mm):·Recessed Depth(mm):·Vertical Tilt(°):·Horizontal Rotation(°):·Light Source:·Lamp Type:·Lamp Type:·Lamp Included:·Lamp Base:·Lume Output(Im):·Colour Temperature(k):·Beam Angle(°):·Lamp Current(A):·Jotal System Power(W):·Luminire Efficacy(Im/K):·Class:·Class:·Chardent Efficacy(Im/K):·Jotal System Power(W):·Power Factor:·Class:·Class:·Chardent Efficacy(Im/K):·Jotal System Power(M):·Power Factor:·Power Factor:·Class:·Class:·Class:·Class:·Pomentify:·Pinmability:·Pinmability:·Pinmability:·Picolicy(Micolicy)·Picolicy·Picolicy·Picolicy·Picolicy·Picolicy·Picolicy·Picolicy·Picolicy·Picolicy·Picolicy·Picolicy·Picolicy·<		-
Environment:InteriorSize(mm)82Cut Out(mm):-Recessed Depth(mm):-Vertical Tilt(°):-Horizontal Rotation(°):-Light Source:-Lamp Type:-Lamp Included:-Lamp Base:-Lumen Output(Im):-Colour Temperature(k):-Beam Angle(°):-Lang Current(A):-Voltage(V):230VTotal System Power(W):-Luminaire Efficacy(Im/W):-Class:-Cass:-EAN Code:-Dimmability:-Power Factor:-Pinability:-P		-
Size(nm)82Cut Out(mm):-Recessed Depth(nm):-Vertical Tilt(°):-Horizontal Rotation(°):-Light Source:-Lamp Type:-Lamp Type:-Lamp Included:-Lamp Life(Hours):-Colour Temperature(k):-Paeam Angle(°):-Lanse:-Voltage(V):-Source:-Lamp Current(A):-Case:-Lamp Current(A):-Gear:-EAN Code:-Soural Efficacy(Im/W):-Finame Efficacy-Dimmability:-Paeam Code:-Soural Efficiency-Class:-Class:-Finame Efficiency-Soural Efficiency-Soural Efficiency-Subschilty: <th></th> <th>-</th>		-
Cut Out(mm):-Recessed Depth(mm):-Vertical Tilt(°):-Horizontal Rotation(°):-Light Source:-Lamp Type:-Lamp Type:-Lamp Included:-Lamp Base:-Lumen Output(Im):-Colour Temperature(k):-Beam Angle(°):-Lamp Current(A):-Voltage(V):230VTotal System Power(W):-Power Factor:-Class:Class 1Gear:-EAN Code:5013874386137Dimmability:-IP20Weight(kg):Weight(kg):0.06kgHousing Material:PlasticMaterial Finish:Natural		
Recessed Depth(mm):-Vertical Tilt(°):-Horizontal Rotation(°):-Light Source:-Lamp Type:-Lamp Type:-Lamp Included:-Lamp Base:-Lumen Output(Im):-Colour Temperature(k):-Beam Angle(°):-Voltage(V):-Zalov230VTotal System Power(W):-Power Factor:-Class:-Class:-Class:-Class:-Pomability:-Pin		82
Vertical Tilt(°):-Horizontal Rotation(°):-Light Source:-Lamp Type:-Lamp Type:-Lamp Included:-Lamp Base:-Lumen Output(Im):-Colour Temperature(k):-Colour Temperature(k):-Beam Angle(°):-Lunse:-Voltage(V):230VTotal System Power(W):-Luminaire Efficacy(Im/W):-Class:Class 1Gear:-EAN Code:5013874386137Dimmability:-IP Rating:N20Weight(kg):0.06kgHousing Material:Natural		-
Horizontal Rotation(°):-Light Source:-Lamp Type:-Lamp Included:-Lamp Base:-Lamp Life(Hours):-Colour Temperature(k):-Craft(Ra):-Beam Angle(°):-Zamp Current(A):-Voltage(V):230VTotal System Power(W):-Luminaire Efficacy(Im/W):-Class:Class 1Gear:-Emergency:-Jimmability:-Power Factor:0.13874386137Dinmability:-Policy-Imability:-Policy-Policy-Facting:PionPion-Ciasting:-Pion-Facting:-Pion-Facting:-Pion-Facting:-Pion-Facting:-Pion-Facting:-Pion-Facting:-Pion-Facting:-Pion-Facting:-Pion-Facting:-Pion-Pion-Pion-Pion-Pion-Pion-Pion-Pion-Pion-Pion-Pion-		-
Light Source:-Lamp Type:-Lamp Included:-Lamp Base:-Lamp Life(Hours):-Lumen Output(Im):-Colour Temperature(k):-Beam Angle(°):-CrI(Ra):-Voltage(V):230VTotal System Power(W):-Luminaire Efficacy(Im/W):-Class:-Cass:-Cass:-Solustion:-Fand Code:-Dimmability:-Pating:-Image Material:-Power Factor:-Class:-Class:-Class:-Dimmability:-Pating:-Pating:-Meight(kg):-Meight Finish:-Natural-		-
Lamp Type:-Lamp Included:-Lamp Base:-Lamp Life(Hours):-Lumen Output(Im):-Colour Temperature(k):-Beam Angle(°):-Lense:-Voltage(V):230VTotal System Power(W):-Power Factor:-Class:Class:Cass:-Cass:-Cass:-Dimmability:-Factore:-Fargency:-Ir Rating:P20Musing Material:NaturalMaterial Finish:Natural		
Lamp Included:-Lamp Base:-Lamp Life(Hours):-Lumen Output(Im):-Colour Temperature(k):-CRI(Ra):-Beam Angle(°):-Lense:-Voltage(V):230VTotal System Power(W):-Power Factor:-Class:Class1Case:-Case:-Dimmability:-Fan Code:-Imagency:-Power Factor:-Class1-Class:-Dimmability:-Power Factor:-Power Factor:-Power Factor:-Dimmability:-Power Factor:-Power Fac		
Lamp Base:-Lamp Life(Hours):-Lumen Output(Im):-Colour Temperature(k):-Colour Temperature(k):-Beam Angle(°):-Lense:-Voltage(V):230VTotal System Power(W):-Power Factor:-Class:Class 1Gear:-Code:-Dimmability:-Faregency:-IP Rating:P020Weight(kg):-Material Finish:Natural		-
Lamp Life(Hours):-Lumen Output(Im):-Colour Temperature(k):-CRI(Ra):-Beam Angle(°):-Lense:-Voltage(V):230VTotal System Power(W):-Lamp Current(A):-Power Factor:-Class:Class 1Gear:-FAN Code:5013874386137Dinmability:-Immability:-Immability:-Power Factor:0.06kgMeight(kg):0.06kgMusing Material:Matural	Lamp Included:	-
Lumen Output(Im):-Colour Temperature(k):-CRI(Ra):-Beam Angle(°):-Lense:-Voltage(V):230VTotal System Power(W):-Power Factor:-Luminaire Efficacy(Im/W):-Gear:Class 1Gear:5013874386137Dimmability:-Pice Tettor:-Pice Tettor:-Dimmability:-Pice Tettor:-Dimmability:-Pice Tettor:-Pice Tettor:-<	Lamp Base:	-
Colour Temperature(k):	Lamp Life(Hours):	-
CRI(Ra):-Beam Angle(°):-Lense:-Voltage(V):230VTotal System Power(W):-Power Factor:-Power Factor:-Class:Class 1Class:-Gear:-EAN Code:5013874386137Dimmability:-Power Factor:0Beargency:-Power Factor:-Power Factor:-Meight(kg):-Dimmability:-Power Factor:-Power Factor:-Power Factor:-Bataria:-Power Factor:-Power Factor:-P	Lumen Output(Im):	-
Beam Angle(°):-Lense:-Voltage(V):230VTotal System Power(W):-Lamp Current(A):-Power Factor:0Class:Class1Gear:-EAN Code:5013874386137Dimmability:-Power Factor:0Dimmability:-Power Factor:0Beam Angle (b):-Dimmability:-Dimmability:-Power Factor:-Beam Angle (b):-Power Factor:-Beam Angle (b):-Autoriant (b):-Beam Angle (b):-	Colour Temperature(k):	
Lense:-Voltage(V):230VTotal System Power(W):-Lamp Current(A):-Power Factor:-Iuminaire Efficacy(Im/W):-Class:Class 1Class:0Ban Code:-Dimmability:-Power Factor:-IP Rating:1920Weight(kg):0.06kgMaterial Finish:Natural		-
Voltage(V):230VTotal System Power(W):-Lamp Current(A):-Power Factor:-Luminaire Efficacy(Im/W):-Class:Class 1Gear:-EAN Code:5013874386137Dimmability:-Fregency:-IP Rating:1P20Weight(kg):0.06kgHousing Material:PlasticMaterial Finish:Natural	Beam Angle(°):	-
Total System Power(W):-Lamp Current(A):-Power Factor:-Luminaire Efficacy(Im/W):-Class:Class 1Class:-Gear:-EAN Code:5013874386137Dimmability:-Fmergency:1P20Keight(kg):0.06kgHousing Material:PlasticMaterial Finish:Natural	Lense:	-
Lamp Current(A):-Power Factor:-Luminaire Efficacy(Im/W):-Class:Class 1Gear:-FAN Code:5013874386137Dimmability:-Emergency:-IP Rating:1P20Weight(kg):0.06kgHousing Material:PlasticMaterial Finish:Natural	Voltage(V):	230V
Power Factor:-Luminaire Efficacy(Im/W):-Class:Class 1Class:-Gear:-FAN Code:5013874386137Dimmability:-Emergency:-IP Rating:N20Weight(kg):0.06kgHousing Material:PlasticMaterial Finish:Natural	Total System Power(W):	-
Luminaire Efficacy(Im/W):-Class:Class 1Gear:-EAN Code:5013874386137Dimmability:-Emergency:-IP Rating:IP20Weight(kg):0.06kgHousing Material:PlasticMaterial Finish:Natural	Lamp Current(A):	-
Class:Class 1Gear:-EAN Code:5013874386137Dimmability:-Fmergency:-IP Rating:IP20Weight(kg):0.06kgHousing Material:PlasticMaterial Finish:Natural	Power Factor:	-
Gear:-EAN Code:5013874386137Dimmability:-Emergency:0IP Rating:1P20Weight(kg):0.06kgHousing Material:PlasticMaterial Finish:Natural	Luminaire Efficacy(lm/W):	-
EAN Code:5013874386137Dimmability:-Emergency:-IP Rating:IP20Weight(kg):0.06kgHousing Material:PlasticMaterial Finish:Natural	Class:	Class 1
Dimmability:-Emergency:-IP Rating:IP20Weight(kg):0.06kgHousing Material:PlasticMaterial Finish:Natural	Gear:	-
Emergency:-IP Rating:IP20Weight(kg):0.06kgHousing Material:PlasticMaterial Finish:Natural	EAN Code:	5013874386137
IP Rating:IP20Weight(kg):0.06kgHousing Material:PlasticMaterial Finish:Natural	Dimmability:	-
Weight(kg):0.06kgHousing Material:PlasticMaterial Finish:Natural	Emergency:	-
Housing Material:PlasticMaterial Finish:Natural	IP Rating:	IP20
Material Finish: Natural	Weight(kg):	0.06kg
	Housing Material:	Plastic
Guarantee: 5 Year Guarantee	Material Finish:	Natural
	Guarantee:	5 Year Guarantee



Images, line drawings and measurements illustrated may, in some cases be approximate and for guidance only. Colour finishes will be maintained as accurately as possible but matching cannot be guaranteed. Illuma Lighting are continually developing and improving its products. Technical specifications subject to change without prior notice. For full terms and conditions visit: <u>https://www.illuma.co.uk/terms.htm</u>

Illuma Lighting (Trading as a divison of Searchlight Electric Ltd.) Sills Road, Willow Farm Business Park Castle Donington Derbyshire, DE74 2US United Kingdom © Illuma 2022

T +44(0) 1332 818 200 F +44(0) 1332 818 222 E sales@illuma.co.uk W www.illuma.co.uk

VAT Registration No. 149697311 Registered in England No: 1169504 Certification BS EN ISO 9001:2008